

ACRYLIC BLEACH

Whitening oxidized or emulsified bituminous coatings.

Product description

ACRYLIC BLEACH is a white coating based on premium acrylic emulsion.

Product Uses

Whitening oxidized or emulsified bituminous coatings such as: FLINTKOTE, mastic asphalt and bituminous sheets used for roof waterproofing.

Packaging

20 kg Bucket



Advantages

- ✓ Protection against sun rays.
- ✓ Prevention of heat absorption.
- ✓ Good adhesion to all types of bitumen and bituminous products.

Technical Specifications

Test type	Test results
Appearance	White paste
Drying time	6-24 hours (respective of weather conditions)

Method of Use

Surface Preparation

- ✓ Verify that the surface to be waterproofed is clean and clear of loose parts, dust, casting shells, concrete morsels, oil and any foreign substance that may impact adhesion. Metal should be cleansed of fat or rust.
- ✓ Roofs coated with new bitumen should be evenly spread with sea sand over the bituminous coating - while still hot.
- ✓ On roofs coated with old bitumen - remove the previous whitening.

Method of application

- ✓ May be applied with an airless sprayer, a brush, a roller or a wiper.
- ✓ Apply two coats of acrylic bleach in an overall quantity of about 300 gr/M². Waiting time between the application of the two coats is about 6-24 hours (respective of weather conditions).



Remarks

- ✓ Do not apply acrylic bleach over coats made of soft bitumen such as 45/55 and/or 20-AC or on a hot roof.
- ✓ Do not apply acrylic bleach in a quantity greater than recommended for one layer.
- ✓ Do not apply in rainy weather or if rain is anticipated in the two days following the completion of the application.
- ✓ Mix before application.
- ✓ Store in a cool, shaded and ventilated place.
- ✓ During product application and drying and the application of other products in its vicinity, make sure the area is properly ventilated.
- ✓ It is recommended to clean tools and hands with soap and water.

Safety instructions

- ✓ Before using the product, you should read the safety instructions and warnings that appear on the product label and the safety data sheet (MSDS) which can be obtained from Pazkar Ltd.
- ✓ Not for human consumption.
- ✓ When using the material, wear personal protective equipment (appropriate clothing, gloves, protective glasses/ face mask).
- ✓ Wash your hands with soap and water immediately after use.

For Safety detailed instructions please refer to Pazkar's safety sheets (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.