

BITOGLASS

Bituminous membrane for prime coating

Product description

A membrane made of bituminous mass reinforced with felt fiberglass, and coated with fine sand on both sides.

Product Uses

The membrane is intended for application under tile and shingle roofs, protection and coating of wooden and concrete roofs, protection of bituminous sealing above and below the ground, protection of bitumen-wrapped steel pipes, multi-layer system sealing of buildings combined with hot or cold bitumen application, protection against capillary water and moisture in brick walls of buildings.

Packaging

30 Rolls



Technical Specifications

Test type	Test Results	Test techniques
Thickness (mm)	1.4	
Reinforcement	Fiberglass	
Roll length, m	20	
Roll width, m	1	
Tensile strength (Length), N/5cm	> 250	ASTM D5147
Tensile strength (Width), N/5cm	> 140	ASTM D5147
% Elongation length	> 1.5	ASTM D5147
% Elongation width	> 1.5	ASTM D5147
Heat resistance, °C	> 100	ASTM D5147
Cold resistance, °C	> 0	ASTM D5147

Method of Use

Surface Preparation

Verify that the surface to be waterproofed is clean and clear of loose parts, dust, casting shells, concrete morsels, oil and any other foreign substance that may interfere with the adhesion.

Method of application

Spread the membranes and bond it with FLEXPAS H bituminous mastic resin or ELASTEX type hot bitumen made by PAZKAR. For integrated waterproofing systems on tile roofs, the reinforcement will be done using nails.

Remarks

- ✓ Store in a shaded, dry, ventilated place in temperature over 5°C.
- ✓ Rolls should be stored only in a vertical position.
- ✓ Do not place or store a pallets over a each other.

For Safety detailed instructions please refer to Pazkar's safety membranes (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.