

## POLYPAZ I3

### Bituminous waterproofing membrane for infrastructures and roads

#### Product description

An SBS type polymer modified bituminous membranes with polyester reinforcement, and a top coat made of Silica sand.

#### Product Uses

- ✓ A sealing and strengthening membrane which is placed at the bottom of the pavement over an active clay infrastructure to prevent water from entering the infrastructure and reduce the possibility of swelling and collapse, and to strengthen the structure of the pavement.
- ✓ A reinforcement membrane on the surface of existing damaged pavements before re-layering, for the purpose of rejecting the reflection of the crack in the new asphalt layer, sealing and reinforcing the pavement.
- ✓ Buffering between the concrete floor and the first block in the construction of walls to prevent the rise of capillary water.

#### Packaging

23 rolls per pallet



#### Advantages

- ✓ High elasticity membrane.
- ✓ Resistance to cyclical fluctuations.
- ✓ High friction between the membrane and the ground.
- ✓ High endurance in subterranean waterproofing.

## Technical Specifications

Properties		
Thickness (mm)	3.0 ± 0.3	
Reinforcement	Especially strong polyester fabric	
Roll length, m	10	
Roll width, m	1	
Longitudinal tensile strength, Newton / 5 cm	> 700	ASTM D5147
Lateral tensile strength, Newton / 5 cm	> 700	ASTM D5147
Elongation length %	> 35	ASTM D5147
Elongation width %	> 35	ASTM D5147
Heat resistance, °C	> 100	ASTM D5147
Elasticity in cold temperatures, °C	> -12	ASTM D5147

## Method of Use

### Preparing the area

The area must be prepared in compliance with Pazkar's special specifications, the Israel Roads' specifications, or the general specifications for construction works (the Blue Book).

### Method of application

- ✓ Application and coverage shall be done in compliance with Pazkar's special specifications, the Israel Road's specifications, or the general specifications for construction works (the Blue Book).
- ✓ Application of the membranes when the ambient temperature is higher than 5°C and rising.
- ✓ The thickness of the cover layer - at least 15 cm.

### Remarks

- ✓ Store in a shaded, dry, ventilated place in temperature over 5°C.
- ✓ Rolls should be stored only in a vertical position.
- ✓ Do not store a pallet over a pallet.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

#### Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at [info@pazkar.co.il](mailto:info@pazkar.co.il). All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.