

SUPERTIGHT

Self-adhesive elastomeric bitumen membrane

Product description

A self-adhesive elastomeric bituminous membrane, reinforced with polyester felt and sand top coating. A thin polyethylene layer is attached to the lower part of the membrane and the overlap strip, which can be easily removed before gluing to the surface and between the overlaps.

Product Uses

Adhesive sealing of foundations, water passages, tin roofs, concrete roofs, OSB boards under tiles or tin roofs, plaster walls and polystyrene boards.

Packaging

23 rolls per pallet



Advantages

Has a particularly high self-adhesive capacity.

Technical Specifications

Properties	SUPERTIGHT 2P	
Thickness (mm)	2	
Reinforcement	polyester fabric	
Roll length, m	20	
Roll width, m	1	
Longitudinal tensile strength, Newton / 5 cm	> 500	ASTM D5147
Lateral tensile strength, Newton / 5 cm	> 300	ASTM D5147
Elongation length %	> 25	ASTM D5147
Elongation width %	> 25	ASTM D5147
Heat resistance, °C	> 100	ASTM D5147
Elasticity in cold temperatures, °C	< -20	ASTM D5147

Method of Use

Preparing the area

Verify that the surface to be waterproofed is clean and clear of loose parts, dust, casting shells, concrete morsels, oil and foreign substances that may impact adhesion. In porous or dusty infrastructures, apply GS474 bituminous primer at a quantity suitable for the type of surface (about 250 gr/m² for an infrastructure made of concrete). Allow the primer to fully dry before gluing the membrane.

Method of application

Membrances must be applied when the ambient temperature is higher than 5°C.

Remarks

- ✓ Store in a shaded, dry, ventilated place in temperature over 5°C.
- ✓ Rolls should be stored only in a vertical position.
- ✓ Do not store a pallet over a pallet.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.