

EXCEL

Cold asphalt mixture for filling potholes and cracks in roads

Product description

Cold asphalt mixture for filling potholes and cracks in asphalt and concrete roads, based on a modified bituminous binder containing polymers, surfactants, organic solvents, and a polymer line.

Product Uses

Repairing potholes and cracks in asphalt and concrete roads under all weather conditions. EXCEL enables the performance of maintenance work on cold asphalt at the highest level.

EXCEL is also suitable for filling ducts dug in the road to install infrastructure and around the covers of sewer ditches. EXCEL can be used in a pit even when it is full of water, but it is recommended only as a last resort and not as an initial solution, since in such an event it is not possible to examine the cleanliness of the pit and the stability of its walls before pouring the material in. In addition, the quality of the sealing of the filling will be questionable.

Packaging

20 kg pail
(Consumption after tightening for a 30/50 cm hole, layer thickness of 5 cm).



Advantages

- ✓ Immediate opening for traffic after the application is finished.
- ✓ Excellent adhesion to the sides of the pit, even when the surrounding is damp.
- ✓ Application under all weather conditions.
- ✓ No need for heating.
- ✓ Remains stable in place for a long period of time.
- ✓ Resistant to surface temperatures ranging between 5°C to 60°C.

Method of use

Surface Preparation

- ✓ Cleaning the pit or crack to a minimum depth of 5 cm.
- ✓ Washing the walls of the pit with water.

Method of application

- ✓ Filling the hole with EXCEL with one layer of 5 cm, or with several pressed layers of 5 cm if the hole is deeper.
- ✓ Tightening the filling with a shovel, and a manual or mechanical press using car wheels depending on the size of the pit and the conditions of the area. **Press each layer separately.**
- ✓ Scattering sand or quarry dust over the entire area of the pit or crack.
- ✓ Hot asphalt mixtures can be applied on top of the EXCEL as customary.
- ✓ After the completion of the above works, the road can be opened to traffic immediately.

Remarks

- ✓ The material's storage period - up to one year from the date of production.
- ✓ The material must be kept in a shielded and well ventilated place.
- ✓ It is recommended to store the product at a temperature higher than 10°C.
- ✓ Do not use the product in parking lots and garages of private homes where a lot of circular movement of vehicles is expected.
- ✓ EXCEL is suitable for application in pits of limited size only.

Safety instructions

- ✓ **Not for human consumption.**
- ✓ **Before using the product, you should read the safety instructions and warnings that appear on the product label and the safety data sheet (MSDS) which can be obtained from Pazkar Ltd.**
- ✓ Not for human consumption.
- ✓ When using the material, wear personal protective gear (appropriate clothing, gloves, protective glasses/ face mask).
- ✓ Wash your hands with soap and water immediately after use.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.