CEMENTPAZ 308i - WHITE

Cementpaz 308i - White

Catalog Number: D91724

Flexible Two-Component Cementitious Waterproofing Material for Walls and Floors

Product description

Cementpaz 308i White is a flexible waterproofing material with high adhesion strength, crack bridging, and excellent substrate adhesion. It retains its properties under extreme thermal conditions and has very high bending and compressive strength. Suitable for pools with water pressure up to 3 atmospheres, it is environmentally friendly and non-toxic. Approved for contact with drinking water - Israeli Standards Institute Standard No. 2545.

Product uses

Waterproofing of bathrooms, showers, and swimming pools. Waterproofing of planters and drainage channels, both positive and negative waterproofing. Waterproofing balconies, stone sealing before casting, and the back of stone using the Bernovich method. Suitable for application on concrete, plaster, and all types of blocks.

Storage

Store the product in a shaded, dry, and cool place. Suitable for use up to 9 months from the production date when stored in its original packaging under recommended conditions.

Packaging

20+5 KG sack\bag



CEMENTPAZ 308i - WHITE

Method of Use

Surface Preparation

Wet the substrate and remove excess water before application. Ensure no oil or diesel stains, and remove loose layers and exposed iron.

Material Preparation

Pour the liquid additive (5 liters) into a mixing bucket. Slowly add the contents of the 20 kg bag while mixing. Mix well to obtain a uniform and workable mixture. Rinse the residue from the container with about 1 liter of water and add it to the mixture.

Method of application

- ✓ Always apply the material in two layers.
- ✓ The quantity for application on a moist surface is about 2-3 kg per square meter.
- ✓ For pools and high water pressure resistance, apply 4 kg per square meter.
- ✓ After the first layer dries, lightly moisten and apply a second layer perpendicular to the first.
- ✓ Wait 24 hours between layers.
- ✓ For stone back waterproofing before casting, clean the back of the stone with a damp cloth or rinse with water.
- ✓ Apply two layers with a brush, waiting for each layer to dry before applying the next.
- ✓ It is recommended to cure the application for 2-3 days several times a day.
- ✓ Clean tools and hands with soap and water after use.

Remarks

- ✓ Do not paint if rain is expected within 72 hours before or after painting or if the wall is wet.
- ✓ Do not paint if the temperature is below 10°C or above 35°C, or if the relative humidity is above 85%.
- ✓ Before use, refer to the safety instructions and warnings on the product label and the Safety Data Sheet (SDS) available from Pazkar Ltd.

Safety instructions

- ✓ **Not for human consumption.**
- ✓ During the use of the material, wear personal protective equipment (Appropriate clothing, gloves, protective glasses / face mask).
- ✓ Wash your hands with soap and water immediately after use.
- ✓ For use at a temperature of up to 40°C.

For Safety detailed instructions please refer to Pazkar's safety data sheets (MSDS)

Warranty
Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product›s suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at infopazkar@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.

Pazkar Ltd. Tel. + 972 4 6423120
Alon-Tavor Indastrial Zone, Afula, 1812001,
infopazkar@pazkar.co.il, www.pazkar.co.il